

QUICKSTART GUIDE



Pioneer Handheld Li-Ion (3600B)

Box may include spare parts kit - no need to install.

To start spraying

1. Fill tank. **Tighten the lid**, to prevent pressure leak.
2. Press | on power switch (top of handle).
3. Press the power button (⏻ near display).
4. To spray, hold the trigger (under the handle). (To spray without constantly holding the trigger: with the trigger held, push in the lock button, then release trigger).
5. Turn the flow dial (left of nozzle) counterclockwise to increase flow rate.
6. **Always keep the fogger upright.**

To stop spraying

1. **Turn the flow dial on the side to 0.**
2. Press O on the handle switch.
3. **Loosen the solution tank lid** to release residual pressure.
4. Empty the tank. We recommend rinsing the tank with water.

Digital display and timer:

(To change mode: Press ⚙ until the mode is highlighted, press ▲, press ⚙ to accept.)

MODE: Normal - tracks how long the motor runs

MODE: Timing - motor turns off after time runs out. To set time: Make sure it says

MODE: Timing, then press ⚙ to select the minutes, press ▲ ▼, press ⚙ to accept.

Storage

1. Clean the solution pipeline by spraying water for 1 minute.
2. Empty the tank.

Need help?

- (Recommended) support@longrayusa.com. We'll respond within 24 hours.
- Or call (415) 830-9494 (9 am - 5 pm Pacific)