

## QUICKSTART GUIDE



### Pulse-jet Thermal Fogger (2nd-gen) (TS35N/NE)

#### 1 Prep

- 1.1 Fill gas tank with regular gasoline, to between  $\frac{1}{4}$  and  $\frac{3}{4}$  full..
- 1.2 Fill solution tank.
- 1.3 The solution tap should be OFF.
- 1.4 Install 4 x D batteries.

#### 2 Startup

- 2.1 Open the gas valve by pulling up.
- 2.2 With your right hand on the ignition button, use your left hand to make full-length pumps, 2 cycles per second.
- 2.3 Pump faster as you hear engine start, until it runs continuously.
- 2.4 Wait 1 minute for the machine to warm up and build solution pressure.
- 2.5 To start fogging, turn solution tap to ON.

#### 3 Shutdown

- 3.1 Turn solution tap to CLEAN.
- 3.2 Wait for fog to stop, then turn solution tap to OFF.
- 3.3 Close the gas valve by pushing down.

**WARNING:** Turn solution tap to OFF before stopping the engine. If the engine stops by itself, turn the solution tap to OFF immediately.

#### Need help?

- (Recommended) [support@longrayusa.com](mailto:support@longrayusa.com). We'll respond within 24 hours.
- Or call (415) 830-9494 (9 am - 5 pm Pacific)